

# 2-Ethylhexanol

## Product Description

2-Ethylhexanol has one primary hydroxyl group. It is a colorless liquid which is soluble in most organic solvents.

## Segment Applications

2-Ethylhexanol is widely used in the production of dioctyl phthalate (vinyl applications), acrylates, 2-ethylhexyl nitrate, lubrication oil additives, mining chemicals, special plasticizers, herbicides and ester oils (non-vinyl application areas).

## Delivery Forms

Drums, IBCs, Iso Containers, Flexi Containers, Bulk

# 2-Ethylhexanol

## Sales Specification

Characteristics	Unit	Specification	Analytical Method
Color	Hazen	Max. 5	ISO 2211- ASTM 1209
Purity as water-free	%	Min. 99.6	GC
Water by wt	%	Max. 0.05	ASTM E 1064
Acid as acetic by wt	%	Max. 0.002	ISO 1385/IV- ASTM D 1613
2-Ethylhexanal	ppm	Max. 200	GC

## General Characteristics

Characteristics	Unit	Typical Value <sup>1</sup>
Molecular weight	g/mol	130.2
Boiling range	°C	183-186
Density at 20 °C	kg/m <sup>3</sup>	832-833

1. Typical values are for information only and not part of sales specification

## Handling and Storage

Perstorp recommends storing 2-Ethylhexanol in stainless steel or aluminum containers. Storage under a nitrogen atmosphere is recommended. The maximum storage temperature has not been determined, but when stored as recommended temperatures up to 40°C is unlikely to present any problem.

CAS No.: 104-76-7

HS No.: 2905 16

REACH registration No.: 01-2119487289-20-0003

Effective date: January 17, 2022

USERS ARE ADVISED TO MAKE THEIR OWN INDEPENDENT DETERMINATION OF THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE. EXCEPT FOR WHAT IS STATED IN PERSTORP'S GENERAL CONDITIONS OF SALE OR SEPARATELY IN A WRITTEN CONTRACT WITH PERSTORP, NO INFORMATION PROVIDED IN THIS DATA SHEET CONSTITUTES A WARRANTY (EXPRESS OR IMPLIED) BY PERSTORP, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.