

# Polyol 4525



## Description

- Polyol 4525 is an alkoxyated polyol
- Tetrafunctional with secondary hydroxyl groups
- Liquid
- Low water content

## Applications

- Crosslinker in polyurethanes
- Precursor for free radical radiation curing monomers and oligomers
- Chemical building block

## Delivery forms

- Steel drums 220 kg, 880 kg/pallet
- Bulk at approximately 50°C

## Sales specification

Hydroxyl number, mg KOH/g <sup>1</sup>	525 ± 15
Water content, % <sup>2</sup>	Max. 0.15
Ash content (Na+K), ppm <sup>3</sup>	Max. 100

## Typical properties

Molecular weight (nominal), g/mole	430 *
Colour, APHA <sup>4</sup>	60
Viscosity (23 °C), mPas <sup>5</sup>	3000
Acid number, mg KOH/g <sup>6</sup>	0.1

\*information only

### Analytical Method

<sup>1</sup> PO 100-1, <sup>2</sup> PO 109-2, <sup>3</sup> PO 103-3, <sup>4</sup> PO 105-4, <sup>5</sup> PO 120-2, <sup>6</sup> PO 110-1  
Analytical methods are available on request

REACH Exempt Polymer

HS no.: 3907 20

Valid from: September 1, 2013